

Overview

HPE 8/24 SAN Switch


The HPE 8/24 SAN Switch delivers affordable and flexible 8 Gb/s connectivity and can be incorporated into an extensive core fabric or placed as an edge switch for SAN environments. The 8/24 SAN Switch is ideal for entry and SMB customers requiring a simple, yet flexible networked storage connectivity solution that will meet evolving requirements. The 8/24 SAN Switch provides the needed connectivity and flexibility at a price point that is affordable, while delivering industry-leading performance for long-term investment protection. It is a solution that is easy to deploy and requires little management time, reducing operational costs.

The 8/24 Base SAN Switch delivers sixteen high performance auto Sensing 1, 2, 4, and 8 Gb/s Fibre Channel ports. With powerful yet flexible capabilities-such as Ports On Demand scalability to 24 ports in an 8-port increment-the 8/24 SAN Switch enables organizations to start small and grow their storage networks in a non-disruptive manner. A fully populated 8/24 SAN Switch with 24 enabled ports provides 384 Gb switching (8 Gb full duplex) capacity for un-congested sustained, 8 Gb full duplex throughput. In addition, organizations can choose to initially deploy 4 Gbit/sec SFPs and upgrade to 8 Gbit/sec SFP+ at a later date when necessary.

The 8/24 SAN Switch with 24 enabled ports may be deployed as a full-fabric switch or in Access Gateway mode, which provides connectivity into any SAN (the default mode setting is a switch). Access Gateway mode utilizes N_Port ID Virtualization (NPIV) switch standards to present Fibre Channel connections as logical devices to SAN fabrics. Attaching through NPIV-enabled switches and directors, the 8/24 SAN Switch with 24 enabled ports in Access Gateway mode can connect to Brocade, McDATA, Cisco, or other SAN fabrics. Key benefits of Access Gateway mode include:

- Improved scalability for large or rapidly growing server and virtual server environments
- Simplified management through the reduction of domains and management tasks
- Fabric interoperability for mixed-vendor SAN configurations that require full functionality

An optional enhanced Power Pack+ software bundle can be purchased separately and includes Fabric Vision, Fabric Watch, ISL Trunking, Extended Fabric and Advanced Performance Monitor. The software bundle provides the SAN administrator with the necessary tools to proactively monitor the health and performance thresholds of the network, while also ensuring the highest levels of security, scalability and manageability. Power Pack+ software enables infrastructure management through a single-pane-of-glass.



HPE 8/24 SAN Switch

What's New

- Updated HPE B-series Network Advisor SKUs to the next suffix (A to B) and added 3 Network Advisor E-LTU SKUs (suffix AE)
- HPE StoreFabric 8/24 8Gb Bundled Fibre Channel switch
- New RoHS 2016 compliant HPE SAN switches

NOTE: Restriction of Hazardous Substances Directive or RoHS is a directive adopted by the European Union that restricts the use of certain hazardous materials in the manufacture of various types of electronic and electrical equipment. The RoHS compliant products with new part numbers listed in this document are functionally equivalent to the corresponding products with old part numbers and are fully interchangeable.

Features and Benefits

Key Features and Benefits

- Superior Performance
 - 8Gb/s full duplex performance to enable up to 384 Gbit/s of uncongested throughput
 - Optional enhanced ISL Trunking combines up to eight ISLs between a pair of switches into a single, logical high-speed trunk capable of up to 64 Gbit/s of throughput
- Flexible storage connectivity
 - The only SAN solutions providing the complete HPE SAN Switch functionality from Embedded to Enterprise. The HPE B-series line of products allows the capability to apply the complete SAN Switch functionality to an affordable entry level SAN deployment and then to grow that deployment to the largest SAN fabric solutions supported by Hewlett Packard Enterprise.
- Reduced Total Cost of Ownership for SAN Infrastructure
 - Enables storage consolidation, simplified management of data center SAN environment
- Broadest range of compatibility with SAN products
 - Multi-vendor server and storage environment
 - Widest range of HPE SAN solutions
 - Interoperability with more than 3 Million HPE SAN Switch installed base
- HPE Power Pack+ Software Bundle (Optional) - Rich, feature packed software that provides the highest supported modular functionality. It includes
 - Fabric Vision
 - Trunking
 - Fabric Watch
 - Advanced Performance Monitor
 - Extended Fabric
- Broadest Range of HPE Packaged SAN Services
 - Mission critical SAN Services SAN-ES
 - Assessment and installation services for security
- Highest integration with Storage Essentials via:
 - SAN Switch API
 - SAN Switch element managers
- Unique Bundle model
 - The HPE StoreFabric 8/24 8Gb Bundled Fibre Channel switch model facilitates ease of ordering with more affordability by offering the HPE 8/24 Base SAN switch along with sixteen 8Gb optical transceivers in one package
 - The HPE StoreFabric 8/24 8Gb Bundled Fibre Channel switch model is offered at a lower price than the sum of the list prices of the HPE 8/24 Base SAN switch and the 8Gb optical transceiver

Models

HPE 8/24 SAN Switch	HPE 8/24 Base 16-port Enabled SAN Switch	AM868C
	HPE StoreFabric 8/24 Bundled FC Switch	C8R07A
	HP 8/8 and 8/24 SAN Switch 8-port Upgrade E-LTU	T5518AAE (Physical License - T5518A)
	HP B-series Entry Switch Power Pack+ E-LTU	T5521AAE (Physical License - T5521A)

NOTE: Some HPE B-series software licenses are now available through the Electronic Delivery (E-Delivery) mechanism. The E-Delivery software licenses with new part numbers listed in this document are functionally equivalent to the corresponding physical licenses with different part numbers. Some software licenses in this document are represented by two part numbers, the first of which is the E-Delivery version (ending with AAE) and the second is the physical version.

Product Highlights

24 non-blocking ports Sixteen enabled ports with expandability to 24 ports; auto-sensing 1, 2, 4, or 8 Gb universal, self-configuring ports (F, FL, E). Can be programmed to fixed 1 Gb, 2 Gb, 4Gb, or 8Gb speed.

Configuration support SAN Switch 8/24 will interoperate with 1Gb/s, 2Gb/s, 4 Gb/s, and 8 Gb/s B-Series SAN Switches running the firmware version defined in the SAN Design Guide:
<http://www.hp.com/go/sandesignguide>

High-availability features

- Hot Code Load Activation

Advanced Fabric Services

- Adaptive Networking
- ISL Trunking (optional)
- Hardware Enforced Zoning
- Web Tools
- Enhanced Group Management (EGM)
- Fabric Watch (optional)
- Extended Fabric (optional)
- Server Application Optimization (SAO)
- SAN Network Advisor (optional)

Manageability

- Web Tools
- Enhanced Group Management (EGM)
- OpenView
- API
- IP
- SNMP
- Radius

Scalability

- The SAN Switch 8/24 scales to the maximum limits defined in the SAN Design Guide.
<http://www.hp.com/go/sandesignguide>

Cabinet Support

- HPE (22U, 36U and 42U) 10000 G2 Series, the Intelligent Series racks and HPE (14U, 22U, 36U, 42U, and 47U) 11000 G2 Series.
NOTE: To order factory integration, add 0D1 after the part number on your sales order.

Product Highlights

Software Components

Frame Filtering An ASIC based capability in the B-series family of switches that enables new applications and features. The switch now has the ability to "view" the first 64 bytes of the Fibre Channel frame. At this time, Frame Filtering enables advanced capabilities such as Advanced Zoning and Advanced Performance Monitoring.

Advanced Zoning In the 8 Gb generation of switches, WWN Zoning and Access Control are enforced by hardware that provides the same simple administration previously enforced only with software. Administrators can organize a physical fabric into logical groups and prevent unauthorized access by devices outside the Zone.

Web Tools Enables organizations to monitor and manage single Fibre Channel switches and small SAN fabrics. Tasks can be performed through a Java-capable Web browser from a standard laptop, desktop PC or workstation from any location within the enterprise.

EGM Enhanced Group Management (EGM) is a FOS license that is included with all B-Series switches and enables multi-switch operations. It helps automate operations across multiple switches to save time and streamline repetitive operations, which are typically prone to error. EGM drives consistency across fabrics, while minimizing the risk associated with potential downtime due to configuration mismatches. EGM provides streamlined troubleshooting for more effective fabric monitoring and diagnosis.

SAN Network Advisor Professional, Professional Plus, and Enterprise enable EGM functionality. Customers have EGM functionality enabled within the hardware product and need only to make the decision around which management application is right for them - SAN Network Advisor Professional, Professional Plus, or Enterprise.

Adaptive Networking Adaptive Networking (AN) is a family of technologies which allow flexible control of traffic movement within the fabric which deliver application aware management of fabric resources. Applications may be used with multiple protocols and multiple classes of service. It includes the following features:

Ingress Rate Limiting:

Allows the ingress bandwidth of a port to be throttled to a rate lower than negotiated with the SAN node. This could be very useful for enterprises offering stepped levels of service and enforcing SLAs.

Quality of Service (QoS):

Enables zones with high, medium, and low priorities within a fabric on a zone by zone basis. This can be very useful for prioritizing array replication over MANs and WANs over less critical traffic.

Traffic Isolation Zones:

Defines paths through a fabric for some or all nodes. Failover allows a non-preferred

Product Highlights

path to be used if the preferred fails. TIZs use failover by default but it can be disabled if traffic should stop if a preferred path fails. TIZ can be used to manually map out traffic flows within a fabric based on application, priority, and topology.

Server Application Optimization

Server Application Optimization (SAO) improves overall application performance for physical servers and virtual machines. SAO, when deployed with B-Series Fibre Channel HBAs, extends B-Series Adaptive Networking from the B-series SAN fabric to the server infrastructure. This delivers application-level, fine-grain Quality of Service (QoS) management to the HBAs and related server applications.

Solution Requirements:

- SAO requires B-series HBA installed in the server
-

Software Components, Optional

Power Pack+ Software Bundle

Includes bundled license for:

- Fabric Vision
- Fabric Watch
- Advanced Performance Monitoring
- Extended Fabric
- ISL Trunking

NOTE: Starting with FOS 7.4.0a, Fabric Watch and Advanced Performance Monitor are replaced by MAPS and Flow Vision respectively. Both are included in Fabric Vision.

Fabric Vision

Fabric Vision offers innovative diagnostic, monitoring and management capabilities to help accelerate new application deployments, address SAN problems before they impact operations and reduce operational costs. It includes

- **Monitoring and Alerting Policy Suite:** A policy-based monitoring tool with pre-built rules and automation that simplifies fabric-wide threshold configuration and monitoring.
- **Flow Vision:** A comprehensive tool that enables administrators to identify, monitor, and analyze specific application data flows without using taps to ensure optimized performance.
- **Health and performance dashboard:** A single customizable screen displayed in HPE SAN Network Advisor that contains all critical SAN information for convenient review and analysis.

Fabric Vision will be included by default in all HPE StoreFabric B-series Fibre Channel switches and Directors bundled with Power Pack+ (with FOS 7.2.0a and later). In all other cases, Fabric Vision can be enabled on HPE StoreFabric B-series Fibre Channel switches and Directors in any one of the following ways

- Application of the Fabric Vision LTU (FOS 7.2.0a and later)
 - Application of the Power Pack+ LTU (FOS 7.2.0a and later)
 - Upgrading existing Switch/Director loaded with Power Pack+ to FOS 7.2.0a or later
 - Upgrading existing Switch/Director loaded with both Advanced Performance Monitor (APM) and Fabric Watch (FW) licenses to FOS 7.2.0a or later
-

Product Highlights

ISL Trunking	For high performance enhanced Trunking, this optional license logically groups up to eight E-ports to provide a high bandwidth trunk between two switches. Each 8Gb switch needs its own license. The switch operating system views the trunk as a single, high bandwidth resource (up to 64 Gb) when routing connections between switches. Connections are load-balanced across the individual links, which comprise the logical trunk group.
Advanced Performance Monitoring	This enabling technology helps administrators monitor and watch specific fabric metrics -- from a SID (Source ID) to a DID (Destination ID) -- so they can fine-tune and scale the fabric more efficiently. Plus, Advanced Performance Monitoring includes the ability for early warning detection of hot spots within the fabric, a powerful tool for maintaining overall balanced performance. NOTE: Advanced Performance Monitoring has been obsoleted in FOS 7.4.0 and later. Users can utilize the Fabric Vision licensed Flow Vision features for performance monitoring.
Fabric Watch	Fabric Watch enables each switch to monitor the SAN for potential faults-and automatically alert network managers to problems before they become failures. Fabric Watch tracks a variety of SAN fabric elements, events, and counters. Monitoring fabric-wide events, ports, SFPs, and environmental parameters permits early fault detection and isolation as well as performance measurement. Each switch in the SAN needs its own Fabric Watch license. NOTE: Fabric Watch has been obsoleted in FOS 7.4.0 and later. Users can migrate their Fabric Watch settings to the Fabric Vision licensed Monitoring and Performance Suite (MAPS) prior to upgrading.
Extended Fabric	Extends all of the scalability, reliability, and performance benefits of Fibre Channel Storage Area Networks (SANs) beyond the native 10 km distance specified by the Fibre Channel standard.

Product Highlights

SAN Network Advisor Professional HPE SAN Network Advisor Professional is a management application available at no-charge and comes with B-series SAN Switches and:

- Allows management of up to two SAN Fabric OS (FOS) fabrics (up to a 300 B-series switch ports and 1000 devices) at a time
- Performs group switch management beyond the scope of Web Tools
- Does not offer management of the SN8000B 8-Slot or DC SAN Backbone Directors

It is targeted for SMB customers that use FOS based SAN fabrics and require a management solution for smaller SANs based = fabrics.

SMB customers that initially start off with SAN Network Advisor Professional and have a small SAN environment may over time feel the need for an enterprise-class product (SAN Network Advisor Professional+ or SAN Network Advisor Enterprise) as their environments start to grow in size and complexity, and as they start to uptake more enterprise-class functionality (such as Fibre Channel Routing, FCIP, etc.). A non-disruptive upgrade path is available from SAN Network Advisor Professional to SAN Network Advisor Professional+ or SAN Network Advisor Enterprise.

SAN Network Advisor Enterprise and Professional+ HPE SAN Network Advisor Enterprise and Professional+ are the enterprise-class product that support FOS products as well as FOS and M-EOS products together. SAN Network Advisor Enterprise provides complete SN8000B 8-Slot Director and DC SAN Backbone Director management including enterprise-class features/environments such as FICON, Fibre Channel Routing, FCIP, adaptive networking, etc while HPE SAN Network Advisor Professional+ provides the same feature set except for support for the SN8000B 8-Slot Director, DC SAN Backbone Director, and FICON.

HPE SAN Network Advisor Enterprise delivers unprecedented scalability, up to 100 fabrics and 15,000 switch ports, while HPE SAN Network Advisor Professional+ scales to 36 SAN Fabrics and 2560 switch ports. To accommodate growth, there is an upgrade available to SAN Network Advisor Enterprise from SAN Network Advisor Professional Plus.

Both offerings provide brand-new features including Adaptive Networking features for quality of service, ingress rate limiting and traffic isolation zones.

HPE Smart SAN for 3PAR HPE Smart SAN, optional software for HP 3PAR, makes end-to-end SAN configuration and management simple and reduces the probability of errors through automation. It is an application embedded in SAN components (array, hosts and switches) that enables 3PAR arrays to orchestrate configuration, settings and policies across the SAN. Smart SAN is only supported with B-series Switches, HPE Storefabric Fibre Channel Adapters (HBAs) and 3PAR storage. HPE Smart SAN for 3PAR through its Target Driven Peer Zoning (TDPZ) feature enables customers to automate peer zoning, resulting in the creation of fewer zones and enables configuration of zones in minutes and not in hours. Through automation, it reduces the probability of errors and potential downtime.

Additional information can be found here:

<http://www8.hp.com/us/en/products/storage-software/product-detail.html?oid=8295863#!tab=features>

NOTE: Supports B-series Brocade 16/8Gb FC switches with FOS 7.4.0a or later.

NOTE: A list of supported HPE FC Adapters can be found at

<https://h20272.www2.hp.com/spock/>

NOTE: Supports 3PAR StoreServ storage with 3.2.2 or later with only 16Gb target ports on HPE 3PAR StoreServ storage.

HPE Support Services and Warranty Information

Warranty (1-1-1) Hardware Warranty - One-year on-site warranty, normal business hours, next business day response, installation not included.

NOTE: The hardware warranty covers firmware and embedded non-saleable software. Saleable software carries its own warranty, see below. Software Warranty - Hewlett Packard Enterprise warrants only that the software media will be free of physical defects for a period of ninety (90) days from delivery.

EXCLUSIVE REMEDY. The entire liability of Hewlett Packard Enterprise and its suppliers and your exclusive remedy for software that does not conform to this Limited Warranty shall be the repair or replacement of the defective media. This warranty and remedy are subject to your returning the defective media during the warranty period to Hewlett Packard Enterprise in the country in which you obtained the software.

For bundled Software Support Your HPE storage product includes comprehensive support and software updates to enhance the performance and availability of your software. Experienced Response Center engineers provide trustworthy advice on issues such as software features and use, problem diagnosis and resolution, and software defect identification.

Software support benefits include:

- Improved productivity of system managers and operators
- Improved system performance and reduced downtime due to software defects
- Expedited problem resolution through expert-level technical resources
- Software and documentation updates
- Electronic access to essential product and support information

Protect your business beyond warranty with HPE Support Services. HPE Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Our integrated portfolio of Services for storage help customers reduce costs, optimize data, streamline storage management, and improve backup and recovery. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new storage solution, giving you full entitlement for the support for need for your IT and business.

Connect your devices

Unlock all of the benefits of your technology investment by connecting your products to Hewlett Packard Enterprise. Achieve up to 77%¹ reduction in down time, near 100%² diagnostic accuracy and a single consolidated view of your environment. By connecting, you will receive 24x7 monitoring, pre-failure alerts, automatic call logging, and automatic parts dispatch. HPE Proactive Care Service and HPE Datacenter Care Service customers will also benefit from proactive activities to help prevent issues and increase optimization. All of these benefits are already available to you with your server storage and networking products, securely connected to Hewlett Packard Enterprise support.

1- IDC

2 - HP CSC reports 2014 - 2015

HPE Support Services and Warranty Information

- Optimized Care** HPE Proactive Care* with 6 hour call-to-repair commitment, three year Support Service
HPE Proactive Care gives customers an enhanced call experience plus helps preventing problems and maintains IT stability by utilizing tailored, proactive reports with recommendations and advice when your products are connected to Hewlett Packard Enterprise. This Service combines three years' proactive reporting and advice with our highest level of hardware support - The Hewlett Packard Enterprise 24x7, six hour hardware call-to-repair. Hewlett Packard Enterprise is the only leading manufacturer who makes this level of coverage available as a standard service offering for your most valuable storage systems.
<https://www.hpe.com/h20195/v2/getpdf.aspx/4aa3-8855enw.pdf>
- Standard Care** HPE Proactive Care* with 24x7 coverage, three year Support Service
HPE Proactive Care gives customers an enhanced call experience plus helps preventing problems and maintains IT stability by utilizing personalized proactive reports with recommendations and advice when your products are connected to Hewlett Packard Enterprise. This Service combines three years' proactive reporting and advice with our 24x7 coverage, four hour hardware response time when there is a problem.
<https://www.hpe.com/h20195/v2/getpdf.aspx/4aa3-8855enw.pdf>
- Basic Care** HPE Foundation Care 24x7, three-year Support Service
HPE Foundation Care 24x7 gives you access to Hewlett Packard Enterprise 24 hours a day, seven days a week for assistance on resolving issues. This service includes need based Hardware onsite response within four hours. Simplify your support experience and make Hewlett Packard Enterprise your first call to help resolve hardware or software problems.
<http://www.hpe.com/h20195/V2/GetDocument.aspx?docname=4AA4-8876ENW&cc=us&lc=en>
- *HPE Proactive Care and HPE Proactive Care Advanced require that the customer connect their devices to make the most of these services and receive all the deliverables.
- Related Services** HPE Installation Service
Provides for the basic hardware installation of Hewlett Packard Enterprise branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.
<http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf>
- HPE SAN Deployment Service
Hewlett Packard Enterprise delivers complete design and implementation services for Fibre Channel, FCoE, FCIP, SAS, and iSCSI SAN connectivity components.
<http://h20195.www2.hpe.com/V2/GetPDF.aspx/5981-8527EN.pdf>
-

HPE Support Services and Warranty Information

eSupport

- HPE eSupport is a portfolio of technology-based services that assist you with managing your business environment - from the desktop to the data center.
Support Portal
The HPE support portal provides one-stop access to the information, tools and services you need to manage the daily operations of your IT environment.

Features include:

- Access to self-solve tools (including search technical knowledge base)
- Efficient logging and tracking of support cases
- Collaboration with other business and IT professionals
- Download of patches and drivers
- Access to diagnostic tools
- Proactive notification of relevant information

Access to certain features of the support portal requires a Hewlett Packard Enterprise service agreement. To access the support portal, visit: <http://www.hp.com/support>

Remote Support Technology (RST)-HPE Remote Support Pack

Taking a more proactive approach to IT support, the HPE Remote Support pack plug-in module easily integrates with HPE Systems Insight Manager to provide a powerful, unified "single pane of glass" solution for onsite and remote management.

HPE Remote Support Pack enhances HPE Systems Insight Manager with intelligent event diagnosis plus the automatic submission of hardware event notifications securely to Hewlett Packard Enterprise support, including acknowledgment and status returns. It adds remote configuration collections to allow the delivery of assessment and proactive services for your SAN storage and HP-UX environments.

Customer Technical Training

Consider education as an integral part of your strategy to get the best return on investment for your HPE storage solution. Hewlett Packard Enterprise offers a variety of training courses on storage software, networking, archiving and disk storage systems. Our classes are available in many delivery modalities from traditional instructor-led courses at one of our 80 training centers worldwide to on-site training customized to your needs or online. <http://www.hp.com/learn/storage>

HPE Services Awards

HPE Services continues to be recognized for service and support excellence by customers, partners, industry organizations and publications around the world. Recent honors and award reflect our services team's dedications, technical expertise, professionalism and uncompromising commitment to customer satisfaction. For a list of all our awards, please visit <http://h20219.www2.hp.com/services/cache/433028-0-0-225-121.htm>

Additional Services Information

For more information about HPE Pointnext operational services for Storage, please visit: <http://www.hp.com/services/storage>

If you have specific questions, contact your local HPE representative. Contact information for a representative in your area can be found at "Contact HPE" <http://www.hp.com>

Family Information

Features	8/8 SAN Switch Base and 8/8 SAN Switch	8/24 SAN Switch Base	SN6000B 16Gb FC Switch and SN6000B 16Gb FC Power Pack+
Targeted Environment	Workgroups, Departments	Workgroups, Departments	Workgroups, Departments
Fibre Channel Port Bandwidth	8Gbit/sec	8Gbit/sec	16Gbit/sec
Aggregate device bandwidth	64-192 Gbit/sec	128-192 Gbit/sec	384-768 Gbit/sec
OS Support	NOTE: Please Refer to SAN Design Guide http://www.hp.com/go/sandesign or http://www.hp.com/go/sandesignguide		
Storage system support	3PAR StoreServ, StoreVirtual 4000, P9000/XP, P6000/EVA, P2000/MSA		
FC Ports	8 Enabled 24 Max	16 Enabled 24 Max	24 or 48 Enabled 48 Max
SFP	B-series	B-series	B-series
Advanced Trunking	Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade
Adaptive Networking	Included	Included	Included
Form factor	1U	1U	1U
Zoning Software	Yes (Included)	Yes (Included)	Yes (Included)
Hot plug, redundant power supplies	No	No	Yes
Hot plug fans	No	No	Yes (integrated with power supply)

Features	8/24 Bundled FC Switch	SN6000B 16Gb Bundled FC Switch
Targeted Environment	Workgroups, Departments	Workgroups, Departments
Fibre Channel Port Bandwidth	8Gbit/sec	16Gbit/sec
Aggregate device bandwidth	128-192 Gbit/sec	384-768 Gbit/sec
OS Support	NOTE: Please Refer to SAN Design Guide http://www.hp.com/go/sandesign or http://www.hp.com/go/sandesignguide	
Storage system support	3PAR StoreServ, StoreVirtual 4000, P9000/XP, P6000/EVA, P2000/MSA	
FC Ports	16 Enabled 24 Max	24 or 48 Enabled 48 Max
SFP	B-series, 16 units included in the box	B-series, 24 units included in the box
Advanced Trunking	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade
Adaptive Networking	Included	Included
Form factor	1U	1U
Zoning Software	Yes (Included)	Yes (Included)

Family Information

Hot plug, redundant power supplies	No	Yes
Hot plug fans	No	Yes (integrated with power supply)

Features Targeted Environment	1606 Extension SAN Switch Data Centers	
Fibre Channel Port Bandwidth	8Gbit/sec	
Ethernet FCIP/FICON OS Support	1Gbit/sec Ethernet Yes, optional license required for FICON NOTE: Please Refer to SAN Design Guide http://www.hp.com/go/sandesign or http://www.hp.com/go/sandesignguide	
Storage system support	3PAR StoreServ, StoreVirtual 4000, P9000/XP, P6000/EVA, P2000/MSA	
FC Ports	4 or 16 Enabled 16 Max	
Ethernet Ports	2 or 6 Enabled 6 Max	
SFP	B-series	
Advanced Trunking Adaptive Networking	Included with Power Pack+ or Optional Upgrade Included	
Form factor	1U	
Zoning Software	Yes (Included)	
Hot plug, redundant power supplies	Yes	
Hot plug fans	Yes	

Features	SN8000B 8-Slot SAN Director Power Pack+	SN8000B 4-Slot SAN Director and 4-Slot SAN Director Power Pack+
Targeted Environment	Cloud Optimized Data Centers	Cloud Optimized Data Centers
Port Bandwidth	Up to 16Gbit/sec	Up to 16Gbit/sec
Aggregate device bandwidth	10.2 Tbit/sec	5.1 Tbit/sec
OS Support	NOTE: Please Refer to SAN Design Guide http://www.hp.com/go/sandesign or http://www.hp.com/go/sandesignguide	
Storage system support	3PAR StoreServe, StoreVirtual 4000, P9000/XP, P6000/EVA, P2000/MSA	
Ports	Up to 512 SFP	Up to 256 SFP
SFP	B-series	B-series
Advanced Trunking	Included with Power Pack	Included with Power Pack or Optional Upgrade

Family Information

Adaptive Networking	Included	Included	
Form factor	14U	9U	
Zoning Software	Yes (included)	Yes (included)	
Hot plug, redundant power supplies	Yes	Yes	
Hot plug fans	Yes	Yes	
Features	Brocade 16Gb SAN Switch for HPE c-Class BladeSystem	Brocade 8Gb SAN Switch for HPE c-Class BladeSystem	Brocade 16Gb Fibre Channel SAN Switch Module for HPE Synergy
Targeted Environment	Enterprise, Datacenters, Workgroups, Departments	Workgroups, Departments	Enterprise, Datacenters, Workgroups, Departments
Port Bandwidth	16Gbit/sec	8Gbit/sec	16 Gbit/sec
Aggregate device bandwidth	448 Gbit/sec (24 ports x 16Gb/s)	192 Gbit/sec	576 Gb/s (36 ports x 16 Gb/s)
OS Support	NOTE: Please Refer to SAN Design Guide http://www.hp.com/go/sandesign or http://www.hp.com/go/sandesignguide		
Storage system Support	3PAR StoreServ, StoreVirtual 4000, P9000/XP, P6000/EVA, P2000/MSA		
Ports	12 external /16 internal	4 or 8 external / 8 or 16 internal	8 SFP+ external, 4 QSFP external /12 internal
SFP	B-series	B-series	B-series
Advanced Trunking	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade
Adaptive Networking	Included	Included	Included
Form factor	Embedded	Embedded	Embedded
Zoning Software	Yes (Included)	Yes (Included)	Yes (Included)
Hot plug, redundant power supplies	Yes, in BladeSystem Enclosure	Yes, in BladeSystem Enclosure	Yes, in Synergy Frame
Hot plug fans	Yes, in BladeSystem Enclosure	Yes, in BladeSystem Enclosure	Yes, in Synergy Frame

Configuration Information

Step 1 - Base Configuration

Select one:

Model Name	Model Description	Part Number
8/24 Base (16) Full Fabric Ports Enabled SAN Switch	HPE 8/24 Base (16) Full Fabric Ports Enabled SAN Switch 8/24 SAN Switch with 16 active ports; rackmount kit; accessory kit (enterprise safety and regulatory information, installation guide, rack-mounting instructions), power cords, single power supply, serial cable, base software of Full Fabric, Advanced Fabric OS, Advanced Web Tools, and Advanced Zoning	AM868C

NOTE: Requires optical transceivers listed below.

8/24 Bundled Fibre Channel Switch	HPE StoreFabric 8/24 Bundled FC Switch 8/24 SAN Switch with 16 active ports; rackmount kit; 16 8Gb optical transceivers, accessory kit (enterprise safety and regulatory information, installation guide, rack-mounting instructions), power cords, single power supply, serial cable, base software of Full Fabric, Advanced Fabric OS, Advanced Web Tools, and Advanced Zoning	C8R07A
---	---	--------

NOTE: Sixteen 8Gb optical transceivers (AJ716B) are included in the package with this switch model

8/24 SAN Switch 8Gb 8-port Upgrade LTU	HPE 8/8 and 8/24 SAN Switch 8Gb 8-port Upgrade LTU 8 port upgrade license for 8/24 SAN Switch (AM868B, AM868C) and 8/24 Bundled Fibre Channel Switch (C8R07A)	T5518AAE (Physical License - T5518A)
--	--	---

Add Software For Fabric OS (FOS) minimum requirements, please refer to:
<http://spock.corp.hp.com/>

B-series 8-24 Port SAN Switch Power Pack+ Upgrade LTU	HPE B-series Entry Switch Power Pack+ E-LTU	T5521AAE (Physical License T5521AAE)
---	---	---

NOTE: Adaptive Networking and Server Application Optimization features are included by default in the switch firmware (FOS 7.2.0a or later) and do not require a separate license

Optional Software:	HPE 8/16Gb Entry Switch Fabric Vision E-LTU	TC509AAE (Physical License - TC509A)
	HPE B-series Entry Switch ISLTrunking E-LTU	T5527AAE (Physical License - T5527A)
	HPE SAN Network Advisor Enterprise Software E-LTU	TC352BAE (Physical License - TC352B)

Configuration Information

HPE SAN Network Advisor Professional Plus Software E-LTU	TC353BAE (Physical License - TC353B)
HPE SAN Network Advisor Professional Plus Upgrade E-LTU	TC354BAE (Physical License - TC354B)
HPE Intelligent Infrastructure Analyzer Software v2 E-LTU	TC472AAE (Physical License - TC472A)

NOTE: Some HPE B-series software licenses are now available through the Electronic Delivery (E-Delivery) mechanism. The E-Delivery software licenses with new part numbers listed in this document are functionally equivalent to the corresponding physical licenses with different part numbers. Some software licenses in this document are represented by two part numbers, the first of which is the E-Delivery version (ending with AAE) and the second is the physical version.

NOTE: HPE SAN Network Advisor software will no longer be shipped as a DVD to customers. Instead, customers will be able to access and download the software from The HPE Product Download web site.

Step 2 - Additional Options

Optical Transceivers

HPE 8Gb Shortwave B-series Fibre Channel 1 Pack SFP+ Transceiver	AJ716B
Distance	OM3 Cable PremierFlex Cable
Maximum	
8Gb performance:	150 meters 150 meters
4Gb performance:	380 meters 380 meters
2Gb performance:	500 meters 500 meters
HPE 8Gb Long Wave B-series 10km Fibre Channel 1 Pack SFP+ Transceiver	AJ717A
HPE B-series 8Gb Extended Long Wave 25km Fibre Channel SFP+ Transceiver 1 Pack	AW538A
HPE 4Gb Short Wave B-series Fibre Channel 1 Pack SFP Transceiver	AJ715A
Distance	OM3 Cable PremierFlex Cable
Maximum	
4Gb performance:	380 meters 380 meters
2Gb performance:	500 meters 500 meters
1Gb performance:	860 meters 860 meters
HP 4Gb Long Wave B-series 30km Fibre Channel SFP Transceiver 1 Pack	AN211A

Configuration Information

USB Device	HPE B-series 4G USB Drive	N9Y63A
Optical Cables	<p>HPE PremierFlex OM4+ Fiber Optic Cables</p> <p>HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable</p> <p>HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable</p> <p>HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable</p> <p>HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable</p> <p>HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable</p> <p>HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable</p> <p>OM3 LC-LC type cables</p> <p>HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable</p> <p>HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable</p> <p>HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable</p> <p>HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable</p> <p>HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable</p> <p>HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable</p> <p>HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable</p>	<p>QK732A</p> <p>QK733A</p> <p>QK734A</p> <p>QK735A</p> <p>QK736A</p> <p>QK737A</p> <p>AJ833A</p> <p>AJ834A</p> <p>AJ835A</p> <p>AJ836A</p> <p>AJ837A</p> <p>AJ838A</p> <p>AJ839A</p>
Accessories	<p>HPE B-Series Switch Rack-Mount Kit</p> <p>NOTE:NOTE: When any of the switch models listed above is ordered, an accessory kit which contains the Rack Mount Kit is included in the package by default. A7511A is required only when the original accessory kit or Rack Mount Kit is unavailable.</p>	A7511A

Fibre Channel Standards And Revisions	<p>FC-AL Rev. 4.5 FC-GS-2 Rev 5.3 FC-PH Rev 4.3 FC-PLDA Rev 2.1 FC-VI Rev 1.5</p> <p>FC-AL-2 Rev 7.0 FC-FG Rev 3.5 FC-PH-2 Rev 7.4 FC-SW Rev 3.3 IPFC RFC 2625</p> <p>FC-FLA Rev 2.7 FC-FH Rev 1.7 FC-PH-3 Rev 9.4</p>
---------------------------------------	--

Technical Specifications

Fibre Channel ports	16 active with optional license to activate 24 universal ports
Scalability	Full fabric architecture: http://www.hp.com/go/sandesignguide
Certified maximum	Refer to SAN Design Guide for current configuration information: http://www.hp.com/go/sandesignguide
Interoperability	<ul style="list-style-type: none">• 4/8 SAN Switch• 4/16 SAN Switch• 4/32 SAN Switch• 4/64 SAN Switch• Core Switch 4/64• DC04 SAN Director• DC SAN Backbone Director• MSA SAN Switch 2/8• SAN Switch 8/8• SAN Switch 8/24• SAN Switch 8/40• SAN Switch 8/80• Encryption SAN Switch• 1606 Extension SAN Switch• 2408 FCoE Converged Network Switch• Brocade 8Gb SAN Switch for HPE BladeSystem c-Class• Brocade 4Gb SAN Switch for c-class HPE BladeSystem• 400 MP Router• HPE MP-Router Blade• SN8000B Director• SN6500B Fibre Channel Switch• SN6000B Fibre Channel Switch• SN3000B Fibre Channel Switch
Performance	8 Gbit/sec line speed, full duplex
Switch core	Non-blocking
Fabric latency	700 nanoseconds with no contention, cut-through routing at 8 Gbit/sec
Maximum frame size	2112-byte payload
Classes of service	Class 2, Class 3, Class F (inter-switch frames)
Port types	FL_Port, F_Port, and E_Port; self-discovery based on switch type (U_Port)
USB	One USB port for system log file downloads or firmware upgrades
Data traffic types	Fabric switches supporting unicast, multicast (255 groups), and broadcast
Media types	B-Series Branded Small Form-Factor Pluggable (SFP)
Laser	Short-wave up to 1,640 ft (500 m); long-wave up to 6.2 mi (10 km) when available
Fabric services	Simple Name Server, Registered State Change Notification (RSCN), Alias Server (multicast); and Zoning, Web Tools, Enhanced group Management, Optional Fabric Watch, ISL Trunking, Adaptive Networking, Extended Fabric, Advanced Performance Monitor, and Server Application Optimization.
Options	SFP media, USB Device
Supported software	Telnet, RADIUS,SNMP, Web Tools, Enhanced Group Management, Advanced Zoning, Fabric Watch, Extended Fabric, Adaptive Networking, Advanced Performance Monitoring, ISL Trunking, Fabric Manager, SAN Network Advisor, Server Application Optimization
Management access	10/100 Ethernet (RJ-45), serial port
Diagnostics	POST and embedded online/offline diagnostics

Technical Specifications

Back-to-front airflow, 1U
power inlet on port
side

Dimensions	Width	42.88 cm (16.88 inches)	
	Height	4.29 cm (1.69 inches)	
	Depth	30.66 cm (12.07 inches)	
	Weight	9.3 lbs with single power supply, without SFP/SFP+	
Environment	Temperature	Operating	0° to 40° C
		Non-operating	-25° to 70° C
	Humidity	Operating	10% to 85% (non-condensing)
		Non-operating	10% to 90% (non-condensing)
	Altitude	Up to 9,800 ft (3,000 m)	
	Shock	20 G, 6 ms, half sine	
Power	Vibration	Operating	.5 G sine, .4grms random 5-500Hz
		Non-operating	2 G sine, 5-500Hz
	AC Input	100 to 240 VAC nominal	
	Supported power range	Nominal	48 Watts
Maximum		57 Watts	
Frequency	47 to 63 Hz		

Summary of Changes

Date	Version History	Action	Description of Change
23-Oct-2017	Version 30	Changed	Care Pack naming and Service and Support- Parts and Materials updated.
07-June-2016	From Version 28 to 29	Changed	Changes made to the Overview and Product Highlights sections.
08-April-2016	From Version 27 to 28	Changed	Service Section was updated.
16-Feb-2016	From Version 26 to 27	Changed	Content updated throughout the QuickSpecs
10-Jun-2014	From Version 25 to 26	Changed	Changes were made throughout the QuickSpecs.
28-Feb-2014	From Version 24 to 25	Changed	Updated the following: added to Step 2, Additional Options A7511A, HPE B-Series Switch Rack Mount Kit and NOTE
09-Dec-2013	From Version 23 to 24	Changed	Model descriptions and product descriptions were revised throughout Configuration Information HPE 8/40 SAN Switch and 8/40 SAN Switch Power Pack+ was removed from Family Information
15-Oct-2013	From Version 22 to 23	Changed	Fabric Vision was added to Product Highlights SN3000B and SN6500B Fibre Channel Switches were added to Interoperability 2408 FCoE CN Switch and 2408 FCoe CN Switch Power Pack+ was removed from Family Information chart
30-Sep-2013	From Version 21 to 22	Changed	Optional Software was revised.
22-Mar-2013	From Version 20 to 21	Changed	Cofiguration Information: Updated Optical Cables section.
08-Mar-2013	From Version 19 to 20	Changed	Family Information: Updated the Storage system support sections.
18-Feb-2013	From Version 18 to 19	Changed	Updated the Family Information Section.
21-Dec-2012	From Version 17 to 18	Changed	Updated the descriptions of two of the model names.
04-Dec-2012	From Version 16 to 17	Changed	Changes were made throughout the QuickSpecs.
12-Oct-2012	From Version 15 to 16	Changed	Change was made to URL in Service and Support, HPE Care Pack, and Warranty Information section.
14-Sep-2012	From Version 14 to 15	Changed	Changes were made in Configuration Information section.

Summary of Changes

13-Aug-2012	From Version 13 to 14	Changed	Changes were made in Overview, Models, Service Support, HPE Care Pack and Warranty Information and in Configuration Information sections.
25-May-2012	From Version 12 to 13	Changed	Updated the following: Additional Options added AJ816B
06-Apr-2012	From Version 11 to 12	Changed	Cabinet Support was revised.
26-Sep-2011	From Version 10 to 11	Changed	Key Features and Benefits, Models, Advanced Fabric Services, Cabinet Support, EGM, Family information, Optical Cables and Interoperability were revised.
08-Jul-2011	From Version 9 to 10	Changed	Updated the following sections: Product Highlights - Advanced Fabric Services; Software Components - EGM, and Software Components optional - SAN Network Advisor; Configuration Information - Step 1 Add Software; Technical Specifications - Management software supported; Technical Specifications - Supported Software. Replaced DCFM references with SAN Network Advisor.
09-Jun-2011	From Version 8 to 9	Removed	Removed "StorageWorks" from the document.
27-Sep-2010	From Version 7 to 8	Added	PremierFlex Cable was added to Step 2.
04-Dec-2009	From Version 6 to 7	Added	HPE 8Gb Long wave B-Series 25km FC SFP+1 Pack was added to Step 2 of the Configuration Information section.
14-Sep-2009	From Version 5 to 6	Added	All mentions of Server Application Optimization and Data Center Fabric Manager Professional Plus (+) throughout the QuickSpecs and Encryption SAN Switch, 1606 Extension SAN Switch and 2408 PCoE Converged Network Switch to the Technical Specifications section.
		Changed	Completely revised Service and Support, HPE Care Pack and Warranty Information and Family Information sections.
26-Jan-2009	From Version 4 to 5	Added	DC04 SAN Director and DC04 SAN Director Power Pack + to the Family Information chart.
		Changed	Completely revised Data Center Fabric Manager Enterprise in the Product Highlights section and Interoperability in the Technical Specifications section.
17-Nov-2008	From Version 3 to 4	Added	Enhanced Group Management (EGM) and Data Center Fabric Manager throughout the QuickSpecs and HPE 8Gb Long Wave B-Series 10km FC SFP +1 Pack to Step 2 in the Configuration Information section.
		Changed	Optional Software in Step 1 of the Configuration Information section.

Summary of Changes

01-Aug-2008	From Version 2 to 3	Added	Extended Fabric to StorageWorks B-series 8-24 Port SAN Switch Power Pack+ Upgrade LTU in Step 1 of the Configuration Information section.
11-Jul-2008	From Version 1 to 2	Changed	Family Information Charts were rewritten and 1Gb performance was removed from Optical Transceivers in Step 2 of the Configuration Information section.