

HPE D3000 Enclosure Components

- PCI Express 3.0 x8 link
- RAID 0, 1, 5, 6, 10, 50, 60, 1 ADM, 10 ADM (Advanced Data Mirroring)
- Mixed Mode (RAID logic drives and HBA physical drives simultaneously)
- Legacy and UEFI boot operation
- UEFI System Utilities (storage configuration)
- Up to 238 physical drives
- Up to 64 logical drives
- HPE Smart Array SR SmartCache (optional license)
- HPE Smart Array SR Secure Encryption (optional license)
- HPE SSD Smart Path
- Rapid Parity Initialization (RPI)
- Rapid rebuild
- Drive Sanitize
- Performance Optimization-Degraded Reads and Read Coalescing
- Power efficiency
- Seamless upgrades from HPE Smart Array S-class and E-class controllers
- FIPS 140-2 Level 1 Implementation Under Test (expected validation complete in 2018)

Smart Array P741m Feature

- Eight (8) 12Gb/s SAS physical links distributed equally across 4 external 2x ports to support up to four 6Gb/s SAS Switches
- 12Gb/s SAS technology delivers up to 1200 MB/s theoretical bandwidth per physical lane
- 6 GB/s SATA technology delivers up to 600 MB/s theoretical bandwidth per physical lane for directly attached SATA drives.
- RAID 0, 1, 10, 5, 50, 6, 60, 1 ADM, 10 ADM
- P741m can support HBA mode which enables deployment of Software Defined Storage such as Microsoft Storage Spaces and VMWare VSAN
- HPE Smart Cache feature (HPE Smart Cache license is not required on P741m) is a controller-based read caching solution in a DAS environment that caches the most frequently accessed data ("hot" data) onto lower latency SSDs to dynamically accelerate application workloads.
- HPE SSD Smart Path feature included in the Smart Array software stack improves SSD read for all RAID levels and RAID 0 write operations by optimizing the path to each SSD attached to the controller
- HPE Secure Encryption, available as an option, is a Smart Array controller-based data encryption solution for ProLiant Gen9 servers that protects sensitive, mission critical data is supported as an option
- PCI Express Gen3 x8 link
- 4 GiBytes Flash Backed Write Cache (FBWC) provides read ahead caching and write back caching with indefinite write cache data retention in the case of unexpected power outage.
- For more information see:
- <http://www8.hp.com/us/en/products/iss-controllers/product-detail.html?oid=7797736#!tab=features>

HPE H222 Host Bus Adapter

- SAS technology delivers high performance and data bandwidth up to 6 Gb/s per physical link
- Mix-and-match SAS and SATA hard drives; deploy drive technology as needed
- PCIe x8 (8 GB/s bandwidth)
- PCIe 3.0 x8 capable
- For more information see:
http://h18004.www1.hp.com/products/QuickSpecs/14337_div/14337_div.pdf

HPE D3000 Enclosure Components

- HPE H241 Host Bus Adapter**
- SAS technology delivers high performance and data bandwidth up to 12Gb/s per physical link
 - Mix-and-match SAS and SATA hard drives; deploy drive technology as needed
 - PCIe 3.0 x8 (8GB/s bandwidth)
 - Enables deployment of Software Defined Storage such as Microsoft Storage Spaces for the D3000 enclosures with Gen9 servers
 - For more information see: [HPE H241 Smart Host Bus Adapter \(QuickSpecs/c04375840.pdf\)](#)
-

- 6Gb SAS BL Switch**
- Hot Pluggable 6Gb/s SAS Switch for HPE c-Class BladeSystem
 - Sixteen internal blade bay ports containing 2x 6Gb/s SAS links
 - Eight external Mini-SAS ports containing 4x 6Gb/s SAS links
 - Use the embedded Virtual SAS Manager GUI or CLI interface to zone switch ports or drive bays to server bays.
 - Supported by c3000 and c7000 c-Class BladeSystem enclosures
 - For more information see: http://h18000.www1.hp.com/products/QuickSpecs/13960_div/13960_div.html
-

- HPE SmartDrive Carrier (Gen8)**
- HPE SmartDrive Carrier features:
- New drive mechanical design
 - Enhanced display of self-describing icons with intuitive and improved LED function
 - Hard drive status indicator
 - Animated drive activity spinner
 - "Do not remove" indicator reduces logical drive failures due to accidental removal of a drive
 - Smart carrier authentication to verify that both drive and carrier are HPE-qualified options
 - Drive error log NVRAM with black-box recorder, for better failure analysis and resolution
-

- RAID**
- Several fault tolerant configurations keep data available and servers running while drives are being replaced - RAID levels that offer fault tolerance include:
- **RAID 50 (RAID 5+0)** protects against failure of one drive (and failure of particular multiple drives). RAID 50 is a nested RAID method that uses RAID 0 striping across RAID 5 arrays. RAID 50 tolerates one drive failure in each spanned array without loss of data. RAID 50 requires less rebuild time than single RAID 5 arrays RAID 50 requires a minimum of six drives.
 - **RAID 60 (RAID 6+0)** allows administrators to split the RAID 6 storage across multiple external boxes. RAID 60 requires a minimum of eight drives. RAID 60 is a nested RAID method that uses RAID 0 block-level striping across multiple RAID 6 arrays with dual distributed parity. With the inclusion of dual parity, RAID 60 will tolerate the failure of two disks in each spanned array without loss of data.
 - **RAID 6 with ADG:** Allocates the equivalent of two parity drives across multiple drives and allows simultaneous write operations Distributed Data Guarding (RAID 5): Allocates parity data across multiple drives and allows simultaneous write operations. Drive Mirroring (RAID 1 and 1+0 Striped Mirroring): Allocates half of the drive array to data and the other half to mirrored data, providing two copies of every file.
-
-

HPE D3000 Enclosure Components

- Dual Domain**
- Dual domain SAS creates redundant pathways from servers to storage devices. The redundant paths created by these configurations reduce or eliminate single points of failure within the storage network. This provides increased levels of high availability with redundant paths from the controller to the drives. Dual domain SAS implementations make it possible to tolerate external cable failure, expander failure, failure in a spanned disk (JBOD) environments. Requires FW v 3.x

Common Slot Power Supply

The D3000 Disk enclosures use the 460W Common Slot Power supply.

HPE's Common Slot Power supplies meet multiple Energy Efficiency Initiatives:

- 460W, 92%: Climate Savers Computing Initiative GOLD and ECOS Consulting 80PLUS GOLD

NOTE: The 80 PLUS program is a unique forum that unites electric utilities, the computer industry, and consumers in an effort to bring energy efficient technology solutions to the marketplace. 80 Plus independently tests power supply efficiency and publicly posts the results on 80Plus.org.

Utilities

The D3000 disk enclosure family utilizes a single, consistent set of utility software for storage and RAID management, setup, configuration and troubleshooting. This consistency reduces the cost of ownership by reducing the training and technical expertise necessary to install and maintain your HPE server storage solution.

Configuration Utilities

Array Configuration Utility (ACU) [On-line for Microsoft and Linux, Remote Web-Based & Off-line]
Option ROM Configuration for Arrays (ORCA),
NetWare ACU CPQONLIN (only online support no Web based support)

Management/Health Utilities

HPE Systems Insight Manager

Array Configuration Utility (ACU)

- Provides a graphical view of HPE drive array configurations.
- Easy to use Wizards for configuration.
- Web Based ACU supports On-Line, Remote Web Based and Off-line configuration.
- Supports on-line configuration for Microsoft, NetWare and Linux.

HPE Systems Insight Manager (SIM)

- Powerful storage, server and server option management tool.
- Monitor storage from a remote central location.
- Browser based Insight Manager 7 provides full access from anywhere on the Intranet, eliminating the need for a dedicated Insight Manager console.

Supported Operating Systems

Gen8/Gen9 HPE ProLiant Servers

NOTE: For information on supported Operating Systems, see the following [Smart Array QuickSpecs](#):

P441: [HPE Smart Array P441 Controller \(QuickSpecs/c04346300.pdf\)](#)

HPE D3000 Enclosure Components

P822: http://h18004.www1.hp.com/products/QuickSpecs/14341_div/14341_div.html

P841: <http://www8.hp.com/us/en/products/iss-controllers/product-detail.html?oid=6995463#!tab=features>

H222: http://h18004.www1.hp.com/products/QuickSpecs/14337_div/14337_div.pdf

H241: [HPE H241 Smart Host Bus Adapter \(QuickSpecs/c04375840.pdf\)](#)

Gen10 HPE ProLiant Servers - Only supported with D3610/D3710

HPE Smart Array P408e-p SR Gen10 (8 External Lanes/4GB Cache) 12G SAS PCIe Plug-in Controller

HPE Smart Array E208e-p SR Gen10 (8 External Lanes/No Cache) 12G SAS PCIe Plug-in Controller

HPE BladeSystem Servers

NOTE: For Information on Supported Operating Systems, see the following Smart Array QuickSpecs:

P731m: http://h18000.www1.hp.com/products/QuickSpecs/14626_div/14626_div.pdf

P741m: <http://www8.hp.com/us/en/products/iss-controllers/product-detail.html?oid=7797736#!tab=features>

Service and Support

Storage Software

HPE StoreVirtual VSA:

With HPE StoreVirtual VSA you can use the power of virtualization to create a virtual array within your host server. Manage it as a single pool of shared storage capacity, and scale it to match your evolving needs. HPE ProLiant Gen9 servers include a 3-year limited license for HPE StoreVirtual VSA software with 1TB of capacity at no extra cost. Simply select to install HPE StoreVirtual VSA software during server setup within Intelligent Provisioning. More information, instructional videos, and free console management software are available at <http://www.hp.com/go/unlock1TB>.

To download the Free 1TB VSA Software see:

<https://h20392.www2.hp.com/portal/swdepot/displayProductInfo.do?productNumber=VSA1TB-9>

For more information and positioning HPE StoreVirtual VSA see:

https://pit.houston.hp.com/PIT/ESSN/Document_Storage/SalesTools/2015-03-17_HPSD_Positioning_Microsoft_WS2012_Storage_Spaces_March_2015_Final.pptx

Microsoft Windows 2012, Storage Spaces:

Software Defined Storage implementation, included in Microsoft Windows 2012 R2 software

Microsoft Storage Spaces can be enabled with the H241 HBA, or the HPE P741m Smart Array Controller (in the HBA mode) and Gen9 servers.

See: the [Windows Server Catalog](#) for the latest supported configurations.

Warranty

Three-year limited parts only warranty, including hardware diagnostic support, pre-failure warranty (coverage of hard drives, memory and processors). The warranty is fully supported by HPE Services and a worldwide network of resellers and service providers. In addition 90-day's getting started software telephone support may be covered under the warranty or available for an additional fee. Enhancements to warranty services are available through HPE Pointnext operational services.

NOTE: The D3000 family has a limited 3 year parts only warranty. SAS and Solid State drives have 3 year warranty. SAS MDL and SATA MDL and SATA Solid State Drives have 1 year warranty.

The D3000 has been designed with customer self-repairable parts to minimize repair time and provide greater flexibility in performing defective parts replacement. Refer to HPE's limited warranty Statement and parts replacement instructions for further details.

<http://h18006.www1.hp.com/products/storageworks/warranty.html>

Service and Support

Services to accelerate time to results

HPE Storage Services bring you a rich portfolio of consulting and support services designed to add value to our core storage products and solutions. We have the know-how and experience to put storage technology to work for you. We work closely with you as your strategic partner, leveraging our full services portfolio to make sure that everything works to optimize your enterprise.

Choose from services aligned to our storage product offerings and lifecycle. From mission-critical onsite services to innovative web-based remote support, you choose the precise level of attention and support your business demands.

Discover, plan, and design Choose from a rich portfolio of services to make the most of HPE D3000 Disk Enclosures so you can efficiently and affordably consolidate, manage, and extract value from

Service and Support

unstructured data.

HPE Services can help you discover needs and create a plan for simplifying the environment, reducing risk, and maximizing your storage investments

HPE Storage Efficiency Analysis - The HPE Storage Efficiency Analysis provides customers with a view of their storage infrastructure and operating environment; highlighting recommendations for improvements. The report provides extensive insight about the existing storage environment, opportunities for efficiency gains, asset aging and replacement through interaction with key decision makers

<https://www.hpe.com/h20195/V2/GetPDF.aspx/4AA3-6727ENW.pdf>

HPE Storage Impact Analysis (SIA): The HPE Storage Impact Analysis service provides a 2-4 week discovery engagement with executive summary presentation. The goal of this service is to help provide customers guidance on storage related issues and develop remediation plans.

<https://www.hpe.com/h20195/V2/GetPDF.aspx/4AA4-1174ENW.pdf>

HPE Storage Modernization Service: The HPE Storage Modernization service is a 4-6 week service that defines the customers envisioned target storage environment based on a proven solution design methodology. Hewlett Packard Enterprise architects will quickly perform tool-assisted automatic discovery and facilitate a two-day strategy workshop with all key stakeholders involved in the storage infrastructure initiative

<https://www.hpe.com/h20195/V2/GetPDF.aspx/4AA3-4620ENW.pdf>

Deploy and integrate

We can help you configure, set up, and efficiently use your HPE D3000 Enclosures as well as help migrate data, improve capacity utilization, and establish information management standards used across backup, replication, and archiving needs.

HPE Storage Data Migration Services - End-to-end data migration service providing seamless discovery, assessment, planning, and design, completely customizable to your organization's storage area network or network attached storage environment and using innovative software to help you migrate to HPE storage quickly and efficiently.

<https://www.hpe.com/h20195/V2/GetPDF.aspx/4AA3-0774ENW.pdf>

HPE Storage and Data Residency Service - Strategic augmentation of your current environment with HPE resources who become your trusted advisor to provide answers that are right for your storage and backup environment.

<http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-9481ENW.pdf>

HPE Proactive Select - A flexible way to purchase services to fit your environment with an extensive menu of HPE Proactive Select event and technical services, such as onsite firmware upgrades, health checks, assessments, and education.

<https://www.hpe.com/h20195/V2/GetPDF.aspx/4AA2-3842ENW.pdf>

Operate and support

Choose the right support to maximize uptime, free up your resources, and achieve improved value-as you get the most out of the existing IT assets while accelerating time-to-revenue.

HPE Proactive Care 24x7 - Hardware and software support services designed specifically for your technology with rapid access to Advanced Solution Center Specialists plus firmware and software management and best practice advice

<https://www.hpe.com/h20195/v2/GetPDF.aspx/4AA3-8855ENW.pdf>

Service and Support

HPE Proactive Care Personalized Support - An option-if you have HPE Proactive Care-to bring increased personalization of the Proactive Care support experience through the assignment of an Account Service Manager (ASM) who provides IT best practice advice to help address IT issues and projects. <https://www.hpe.com/h20195/V2/GetPDF.aspx/4AA4-3446ENW.pdf>

HPE Support Plus 24 - Support for environments where proactive help from Hewlett Packard Enterprise is not required, with 24x7 hardware and software support onsite that includes third-party support with a maximum four-hour onsite response. <https://www.hpe.com/h20195/V2/GetPDF.aspx/5981-6638EN.pdf>

HPE Education Services - Comprehensive training for new, as well as experienced, storage administrators designed to expand your skills and keep you up to speed with the latest storage and virtualization technology from HPE Storage. <http://education.hp.com/curr-storsan.htm>

Optimized Care - Delivers the highest levels of performance and stability through deployment and proactive management practices

Choose from three levels of operate and support care

HPE Proactive Care 24x7-Plus, 20 credits per year

Additional options -HPE Proactive Care Personalized Support (once per Proactive Care support new environment), an additional day of HPE Personalized Support, and 10 additional HPE Proactive Select credits per year

Standard Care - maintains high level of uptime, along with expert help to cut the cost and complexity of implementation and support

HPE Proactive Care 24x7-Plus, 10 credits per year

Additional options -HPE Proactive Care Personalized Support (once per Proactive Care support new environment), an additional day of HPE Personalized Support, and 10 additional HPE Proactive Select credits per year

Basic Care - Minimum recommended support

HPE Support Plus 24- Plus, 10 credits per year

Additional options - 10 HPE Proactive Select credits per year

Remote Support Automation

HPE Automation provides 24x7 coverage, proactive problem prevention, accurate problem diagnosis and faster problem resolution, as well as interactive support portals and tools. This is an integral, and cost-free, part of your HPE support relationship and we are continually investing in additional cutting-edge capabilities to make it better.

For more

Service and Support

information

<http://www.hp.com/services/storage>

To learn more on HPE Storage Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. HPE Pointnext operational services are sold by HPE and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.
- Customers purchasing from a commercial reseller can find HPE Pointnext operational services at: <http://www.hp.com/go/lookuptool>

Configuration Information

Step 1: Base Configuration

Model	Model Description	Part Number
HPE D3610 Enclosure	HPE D3610 Enclosure NOTE: Gen10 branded D3000 enclosure for use with Gen10 ProLiant servers	Q1J09A
HPE D3610 SAS Dual Port MDL drives bundles	HPE D3610 w/12 4TB 12G SAS 7.2K LFF (3.5in) Midline Smart Carrier HDD 48TB Bundle	Q1J11A
	HPE D3610 w/12 6TB 12G SAS 7.2K LFF (3.5in) Midline Smart Carrier HDD 72TB Bundle	Q1J12A
	HPE D3610 w/12 8TB 12G SAS 7.2K LFF (3.5in) Midline Smart Carrier HDD 96TB Bundle	Q1J13A
	HPE D3610 w/12 10TB 12G SAS 7.2K LFF (3.5in) Midline Smart Carrier HDD 120TB Bundle	Q1J14A
HPE D3600 Enclosure	HP D3600 Enclosure	QW968A
HPE D3710 Enclosure	HPE D3710 Enclosure NOTE: Gen10 branded D3000 enclosure for use with Gen10 ProLiant servers.	Q1J10A
HPE D3710 SAS Dual Port Drive Bundles	HPE D3710 w/25 600GB 12G SAS 10K SFF (2.5in) Enterprise Smart Carrier HDD 15TB Bundle	Q1J15A
	HPE D3710 w/25 1.2TB 12G SAS 10K SFF (2.5in) Enterprise Smart Carrier HDD 30TB Bundle	Q1J17A
	HPE D3710 w/25 1.8TB 12G SAS 10K SFF (2.5in) Enterprise Smart Carrier HDD 45TB Bundle	Q1J18A
	HPE D3710 w/25 1TB 6G SAS 7.2K SFF (2.5in) Midline Smart Carrier HDD 25TB Bundle	Q1J19A
	HPE D3710 w/25 2TB 6G SAS 7.2K SFF (2.5in) Midline Smart Carrier HDD 50TB Bundle	Q1J20A
HPE D3700 Enclosure	HP D3700 Enclosure	QW967A

Configure to Order Program Information

Configuration Information

The HPE D3000 models and options may or may not be factory installed in a rack with add-on controllers, and hard drives. The D3000 enclosures may be integrated with ProLiant servers or as standalone storage.

Model	Model Description	Part Number
HPE D3610	HPE D3610 Enclosure	Q1J09A-#0D1
HPE D3710	HPE D3710 Enclosure	Q1J10A-#0D1
HPE D3600	HPE D3600 Enclosure	QW968A-#0D1
HPE D3700	HPE D3700 Enclosure	QW967A-#0D1

Step 2: Array Controllers

Smart Array Controllers Supported	Description	Part Number
	Gen8/Gen9 HPE ProLiant Servers	
	HP Smart Array P441/4GB FBWC 12Gb 2-ports Ext SAS Controller	726825-B21
	HP Smart Array P841/4GB FBWC 12Gb 4-ports Ext SAS Controller	726903-B21
	Gen10 HPE ProLiant Servers - only supported with D3610/D3710 Enclosures	
	HPE Smart Array P408e-p SR Gen10 (8 External Lanes/4GB Cache) 12G SAS PCIe Plug-in Controller	804405-B21
	NOTE: Firmware version 2.0 or higher required on the listed Smart Array Controllers.	
	NOTE:	
	<ul style="list-style-type: none"> Up to eight (8) D3600 can be cascaded for a total of 96 drives. Up to eight (8) D3700 can be cascaded for a total of 200 drives. Smart Array Controllers P421, P43, P44, P822 and P841 support the mixing of the D3600 and the D3700 for expansion. Supports eight (8) D3600 and/or D3700 allowing for expansion up to 148 drives (total of 8 enclosures in any combination). 	

HPE Host Bus Adapters (HBAs)	HP H222 Host Bus Adapter	650926-B21
	HP H241 12Gb 2-ports Ext Smart Host Bus Adapter	726911-B21
	Gen10 HPE ProLiant Servers	
	HPE Smart Array E208e-p SR Gen10 (8 External Lanes/No Cache) 12G SAS PCIe Plug-in Controller	804398-B21

Smart Array Controllers /Switches	BladeSystem Servers	
	HP Smart Array P731m/2GB FBWC 6Gb 4-ports Ext Mezzanine SAS Controller	698535-B21
	HP Smart Array P741m/4GB FBWC 12Gb 4-ports Ext Mezzanine SAS Controller	726782-B21

Configuration Information

HP 6Gb SAS Switch Single Pack for HP BladeSystem c-Class	BK763A
HP 6Gb SAS Switch Dual Pack for HP BladeSystem c-Class	BK764A

NOTE: D3600/D3700 6Gb SAS BL Switch support requires Firmware version 1.34.

NOTE: HPE Smart Array P741m/4GB FBWC controller option kit does not include the HPE Smart Storage Battery the backup power source necessary to protect the data on the Flash-backed Write Cache. HPE Smart Storage Battery is an item that has to be purchased separately if this is the first P-series Smart Array controller on your Gen9 server.

Step 3: Choose HPE ProLiant Servers/MSA Arrays/HPE Integrity Servers

HPE ProLiant Server Compatibility	D3600/D3700 only HPE ProLiant Servers: For up to date compatibility, see the following URL for complete Smart Array P431, P441, P822, P841, P721m, P741m Controller and HBA H221, H222 compatibility and support information: http://h18004.www1.hp.com/products/servers/proliantstorage/arraycontrollers/index.html
--	---

BladeSystem Server Compatibility - P731m Controller	HPE ProLiant BL420c Gen8 HPE ProLiant BL460c Gen8 HPE ProLiant BL465c Gen8 HPE ProLiant BL660c Gen8 NOTE: For BL420c Gen8 & BL460c Gen8 - P731m is a Type B mezzanine .It can only be installed on mezzanine slot 2 which requires a second processor for functionality. The BL420c, BL465c, and BL460c Gen8 can only support one Type B mezzanine. For BL465 Gen8 - P731m is a Type B mezzanine and can only be installed on mezzanine slot 2 For BL660c Gen8 - P731m is a Type B mezzanine. It can only be supported on mezzanine slot 2 and mezzanine slot 3. The BL660c Gen8 can support up to two Type B mezzanines. NOTE: For more information on internal vs external connections, please refer to proper blade QuickSpecs visit: http://h18000.www1.hp.com/products/QuickSpecs/division/12534.html
--	---

Step 4: Choose Hard Drives

HPE D3600/D3610 Enclosures - Large Form Factor (LFF)

15K SAS LFF (3.5in) Hard Disk Drives

HP 300GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty Hard Drive	737261-B21
HP 450GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty Hard Drive	737394-B21
HP 600GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty Hard Drive	765424-B21

7.2K SAS Midline LFF (3.5in) Hard Disk Drives

Configuration Information

HPE 10TB 12G SAS 7.2K rpm LFF (3.5-inch) SC Midline 512e 1yr Warranty Hard Drive	857644-B21
HPE 8TB 12G SAS 7.2K rpm LFF (3.5-inch) SC Midline 512e 1yr Warranty Hard Drive	819201-B21
HPE 8TB 12G SAS 7.2K rpm LFF (3.5-inch) SC 512e Helium 1yr Warranty Hard Drive	861590-B21
HPE 6TB 12G SAS 7.2K rpm LFF (3.5-inch) SC 1yr Warranty Hard Drive	861754-B21
HPE 6TB 12G SAS 7.2K rpm LFF (3.5-inch) SC 1yr Warranty Hard Drive	846514-B21
HPE 6TB 12G SAS 7.2K rpm LFF (3.5-in) 3yr SC SGT Kit	808727-B21
HPE 4TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	872487-B21
HPE 4TB 12G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	818367-B21
HPE 2TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	872485-B21
HPE 2TB 12G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	818365-B21
HPE 1TB SAS 12G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	846524-B21
7.2K SATA LFF (3.5in) Hard Disk Drives	
HPE 10TB 6G SATA 7.2K rpm LFF (3.5-inch) SC 512e 1yr Warranty Hard Drive	857648-B21
HPE 8TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 512e 3yr Warranty Hard Drive	857370-B21
HPE 4TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty 512e Digitally Signed Firmware HDD	861752-B21
HPE 4TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	872491-B21
HP 1TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	861691-B21
HPE 2TB SATA 6G Midline 7.2K LFF (3.5in) SC 1yr Wty Digitally Signed Firmware HDD	872489-B21
HP 3TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive	861693-B21
Large Form Factor Solid State Drives	
SAS Mixed Use LFF (3.5in) Solid State Drive	
HPE 800GB SAS 12G Mixed Use LFF (3.5in) 3yr Wty Digitally Signed Firmware SSD	872378-B21
SATA Read Intensive LFF (3.5in) Solid State Drive	
HPE 3.84TB SATA 6G Read Intensive LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	868830-B21
HPE 1.6TB SATA 6G Read Intensive LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	869388-B21
HPE 480GB 6G SATA Read Intensive LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	869380-B21
SATA Mixed Use- LFF (3.5in) Solid State Drive	

Configuration Information

HPE 1.92 SATA Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	875480-B21
HPE 960GB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	872350-B21
HPE 480GB SATA 6G Mixed Use LFF (3.5in) SCC 3yr Wty Digitally Signed Firmware SSD	872346-B21
SATA Write Intensive LFF (3.5in) Solid State Drive	
HPE 1.6TB SATA 6G Write Intensive SFF (2.5in) SCC 3yr Wty Digitally Signed Firmware SSD	872365-B21
HPE 800GB SATA 6G Write Intensive SFF (2.5in) SCC 3yr Wty Digitally Signed Firmware SSD	872361-B21
HPE 400GB SATA 6G Write Intensive SFF (2.5in) SCC 3yr Wty Digitally Signed Firmware SSD	872357-B21
HPE 400GB 6G SATA Write Intensive-3 LFF 3.5-in SCC 3yr Wty Solid State Drive	867817-B21
HPE D3700/D3710 - Small Form Factor (SFF)	
10K SAS SFF (2.5in) Hard Disk Drives	
HPE 1.8TB SAS 12G Enterprise 10K SFF (2.5in) SC 3yr Wty 512e DS HDD	872481-B21
HPE 1.8TB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 512e 3yr Warranty Hard Drive	791034-B21
HPE 1.2TB SAS 12G Enterprise 10K SFF (2.5in) SC 3Yr Wty DS HDD	872478-B21
HPE 1.2TB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	781518-B21
HPE 900GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	785069-B21
HPE 600GB SAS 12G Enterprise 10K SFF (2.5in) SC 1yr Wty DS HDD	872477-B21
HPE 600GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	781516-B21
HPE 300GB SAS 12G Enterprise 10K SFF (2.5in) SC 3Yr Wty DS HDD	872475-B21
HPE 300GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	785067-B21
15K SAS SFF (2.5in) Hard Disk Drives	
HPE 300GB SAS 12G Enterprise 15K SFF (2.5in) SC 3yr Wty DS HDD	870753-B21
HP 300GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759208-B21
HP 450GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759210-B21
HP 600GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759212-B21
HPE 600GB SAS 12G Enterprise 15K SFF (2.5in) SC 3yr Wty DS HDD	870757-B21
HPE 600GB SAS 12G Enterprise 15K SFF (2.5in) SC 3yr Wty 512e DS HDD	870763-B21

Configuration Information

HPE 900GB SAS 12G Enterprise 15K SFF (2.5in) SC 3yr Wty DS HDD	870759-B21
HPE 900GB SAS 12G Enterprise 15K SFF (2.5in) SC 3yr Wty 512e DS HDD	870765-B21
7.2K SAS Midline SFF (2.5in) Hard Disk Drives	
HPE 2TB 12G SAS 7.2K rpm SFF (2.5-inch) SC 512e 1yr Warranty Hard Drive	765466-B21
HPE 1TB SAS 12G Midline 7.2K SFF (2.5in) SC 1yr Wty 512e Digitally Signed Firmware HDD	765464-B21
HPE 1TB 12G SAS 7.2K rpm SFF (2.5-inch) SC 512e 1yr Warranty Hard Drive	832514-B21
7.2K SATA Midline SFF (2.5in) Hard Disk Drives	
HPE 1TB 6G SATA 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	765453-B21
HPE 2TB 6G SATA 7.2K rpm SFF (2.5-inch) SC 512e 1yr Warranty Hard Drive	765455-B21
NOTE: SATA drives are single ported and therefore do not have a fail-over path intrinsic to their design. Only Dual Port (DP) SAS drives will work in the Dual Domain environment.	
Small Form Factor 12G SAS Solid State Drives	
SAS Mixed Use SFF (2.5in) Solid State Drives	
HPE 3.2TB SAS 12G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	873367-B21
HPE 3.2TB SAS 12G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872386-B21
HPE 1.6TB SAS 12G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	873365-B21
HPE 1.6TB SAS 12G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872382-B21
HPE 800GB SAS 12G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	873363-B21
HPE 800GB SAS 12G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872376-B21
HPE 400GB SAS 12G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	873359-B21
HPE 400GB SAS 12G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872376-B21
SAS Read Intensive SFF (2.5in) Solid State Drives	
HPE 7.68TB SAS Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	870144-B21
HPE 3.84TB SAS 12G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872394-B21
HPE 3.84TB SAS Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	875330-B21
HPE 1.92TB SAS 12G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872392-B21
HPE 1.92TB SAS Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	875326-B21

Configuration Information

HPE 960GB SAS 12G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872390-B21
HPE 960GB SAS Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	875313-B21
HPE 480GB SAS Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	875311-B21

SAS Write Intensive SFF (2.5in) Solid State Drives

HPE 1.6TB SAS 12G Write Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	873357-B21
HPE 800GB SAS 12G Write Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	873355-B21
HPE 400GB SAS 12G Write Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	873351-B21

NOTE: Number of drives is limited to twenty five (25) per controller.

NOTE: SAS Solid State drives are dual path and dual domain.

NOTE: Cascading is supported in both single and dual domain environments.

Small Form Factor 6G SATA Solid State Drives

SATA Mixed Use- SFF (2.5in) Solid State Drives

HPE 1.92TB SATA 6G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872352-B21
HPE 480GB SATA 6G Mixed Use SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872344-B21

SATA Read Intensive- SFF (2.5in) Solid State Drives

HPE 1.92TB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed FirmwareSSD	868826-B21
HPE 1.92TB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed FirmwareSSD	871770-B21
HPE 1.6TB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	869386-B21
HPE 960GB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed FirmwareSSD	871768-B21
HPE 960GB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	868822-B21
HPE 480GB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	869378-B21
HPE 480GB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	868818-B21
HPE 240GB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	868814-B21
HPE 150GB SATA 6G Read Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	869374-B21

SATA Write Intensive- SFF (2.5in) Solid State Drives

HPE 1.6TB SATA 6G Write Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872363-B21
--	------------

Configuration Information

HPE 800GB SATA 6G Write Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872359-B21
HPE 400GB SATA 6G Write Intensive SFF (2.5in) SC 3yr Wty Digitally Signed Firmware SSD	872355-B21

NOTE: Number of drives is limited to twenty five (25) per controller.

Step 5: Choose Rack Option

Refer to the HPE Infrastructure products page for more information on HPE racks and rack options:
<http://h18004.www1.HPE.com/products/servers/platforms/rackandpower.html>

Step 6: Choose Cables

Cable Options Cables to be used for connecting the HPE D3600/D3700 with the HPE Smart Array P822, Controllers and H222 Host Bus Adapters

HPE 0.5m External Mini SAS High Density to Mini SAS Cable	691971-B21
HPE 1.0m External Mini SAS High Density to Mini SAS Cable	716189-B21
HPE 2.0m External Mini SAS High Density to Mini SAS Cable	716191-B21
HPE 4.0m External Mini SAS High Density to Mini SAS Cable	716193-B21

Cables to be used for connecting D3600/D3700/D3610/D3710 with the Smart Array P431, P441, P841, P731m, P741m, E208e, P408e Controllers, and H241 Host Bus Adapter (HD connector)

HPE External 1.0m (3ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable	716195-B21
HPE External 2.0m (6ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable	716197-B21
HPE External 4.0m (13ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable	716199-B21

* #0D1 will appear after this part number on your sales order if factory integration is indicated.

Power Cord Options

If customers require a power cord other than the included PDU style cords, they can check the power cord matrix for the appropriate SKU. See the following power cord matrix for details
<http://www.hpe.com/products/powercords>.

NOTE: An optional longer 2meter PDU power cable (C14 to C13 style connector) for customers who would like additional length for connections to existing power distribution modules located on the right side of the rack. This is purely optional as the included .7meter power cables will also reach the right sides of the rack. (D3700 power supplies are on the left side of the enclosures). If desired, the quantity to order is 1 AF573A HPE RDNT 2m,10A, C13-C14 JMPR CORD

Technical Specifications

LED Indicators for HDDs	HPE SmartDrive Carrier Drives	
LED Indicators on Front Panel	Bi-color green/amber for health/fault Blue for UID Heartbeat LED Fault LED UID button/LED	
LED Indicators on Rear Panel	I/O Module LED (2) identify/On/Fault; Port (2) Link good/ link fault UID button/LED Heartbeat LED Fault LED Fan LED Power supply LED	
Host Interface	8 x wide SAS 12Gb/s ports	
Maximum Number of Drives	Up to 12 3.5 inch (D3600/D3610) or 25 2.5 inch (D3700/D3710) SAS or SATA drives Up to 25 2.5 inch (Solid State Drives per controller)	
Acoustics Noise	Listed are the declared A-Weighted sound power levels (LWAd) and declared average bystander position A-Weighted sound pressure levels (LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and declared in accordance with ISO 9296 (ECMA 109). The listed sound levels apply to standard shipping configurations. Additional options may result in increased sound levels.	
	Idle Acoustic Noise (sound power)	LWAd= 7.0 B
	Idle Acoustic Noise (sound pressure)	LpAm - 53 dBA
	Operating Acoustic Noise (sound power)	LWAd= 7.0 B
	Operating Acoustic Noise (sound pressure)	LpAm - 53 dBA
Temperature Range	Operating	50° to 104° F (10° to 40° C)
	Shipping	-22° to 149° F (-30° to 65° C)
		NOTE: Rated 1°C per 1000 feet of elevation to 10,000 ft.
Relative Humidity	Operating	10% to 90%
	Non-operating	0% to 95%
Maximum wet bulb temperature	Long-term storage (operating)	82.4° F (28° C)
	Short-term storage (non-operating)	101.6° F (38.7° C)
Input Power Requirements	Rated Input Voltage	100 to 240 VAC (Common- slot Power Supply)
	Rated Input Frequency	50 to 60 Hz (Common-slot Power Supply)
	Rated Input Current	6A/3A
	Input Power max	403W

Technical Specifications

Heat Dissipation (maximum)	1331/Btu/hr.1160.Btu/hr								
	NOTE: standard conversion from Watts to Btu/hr = 3.413 Btu/hr per Watt.								
RAID Support	See QuickSpecs for Smart Array Controllers P431, P822, P731m, P408e-p, E208e-p http://h18004.www1.hp.com/products/servers/proliantstorage/arraycontrollers/index.html								
	NOTE: For up to date compatibility, see the following URL for complete Smart Array Controller compatibility and support information: http://h18006.www1.hp.com/products/servers/proliantstorage/arraycontrollers/index.html								
Upgradeable Firmware	Yes, Offline only. Firmware updates available through hp.com								
Disk Drives and Enclosure Protocol Support	HPE 3.5 inch (D3600/D3610) or 2.5 inch (D3700/D3710) SAS 6/12Gb/s								
I/O Module	<table border="0"> <tr> <td>Connector Type</td> <td>IPass (mini-SAS)</td> </tr> <tr> <td>Number of Ports</td> <td>Two (one IN, other is OUT)</td> </tr> <tr> <td>Bandwidth</td> <td>SAS-3 (12Gb/s)</td> </tr> <tr> <td>Protocols supported</td> <td>SAS 3.0</td> </tr> </table>	Connector Type	IPass (mini-SAS)	Number of Ports	Two (one IN, other is OUT)	Bandwidth	SAS-3 (12Gb/s)	Protocols supported	SAS 3.0
Connector Type	IPass (mini-SAS)								
Number of Ports	Two (one IN, other is OUT)								
Bandwidth	SAS-3 (12Gb/s)								
Protocols supported	SAS 3.0								
HPE D3600/ Enclosure	<table border="0"> <tr> <td>2U Rack Form Factor</td> <td>Large Form Factor</td> </tr> <tr> <td>Dimensions (HxWxD)</td> <td>3.44" x 17.64" x 23.54" in (8.7 x 44.8 x 59.8 cm)</td> </tr> <tr> <td>Weight (base unit)</td> <td>38 lb (17.2 kg)</td> </tr> <tr> <td>Weight (with all LFF drives)</td> <td>60 lb (27.2 kg)</td> </tr> </table>	2U Rack Form Factor	Large Form Factor	Dimensions (HxWxD)	3.44" x 17.64" x 23.54" in (8.7 x 44.8 x 59.8 cm)	Weight (base unit)	38 lb (17.2 kg)	Weight (with all LFF drives)	60 lb (27.2 kg)
2U Rack Form Factor	Large Form Factor								
Dimensions (HxWxD)	3.44" x 17.64" x 23.54" in (8.7 x 44.8 x 59.8 cm)								
Weight (base unit)	38 lb (17.2 kg)								
Weight (with all LFF drives)	60 lb (27.2 kg)								
HPE D3700 Enclosure	<table border="0"> <tr> <td>2U Rack Form Factor</td> <td>Small Form Factor</td> </tr> <tr> <td>Dimensions (HxWxD)</td> <td>3.44" x 17.64" x 21.48" in (8.7 x 44.8 x 54.6 cm)</td> </tr> <tr> <td>Weight (base unit)</td> <td>38 lb (17.2 kg)</td> </tr> <tr> <td>Weight (with all SFF drives)</td> <td>54.90 lb (24.9 kg)</td> </tr> </table>	2U Rack Form Factor	Small Form Factor	Dimensions (HxWxD)	3.44" x 17.64" x 21.48" in (8.7 x 44.8 x 54.6 cm)	Weight (base unit)	38 lb (17.2 kg)	Weight (with all SFF drives)	54.90 lb (24.9 kg)
2U Rack Form Factor	Small Form Factor								
Dimensions (HxWxD)	3.44" x 17.64" x 21.48" in (8.7 x 44.8 x 54.6 cm)								
Weight (base unit)	38 lb (17.2 kg)								
Weight (with all SFF drives)	54.90 lb (24.9 kg)								
D3600/D3700	<table border="0"> <tr> <td>Shipping package dimensions</td> <td>D3600 - 11.13" x 23.75" x 38.12" (LFF)</td> </tr> <tr> <td></td> <td>D3700 - 11.13" x 23.75" x 36.12" (SFF)</td> </tr> <tr> <td>Shipping weight (Gross)</td> <td>78lbs (35.38kg)</td> </tr> </table>	Shipping package dimensions	D3600 - 11.13" x 23.75" x 38.12" (LFF)		D3700 - 11.13" x 23.75" x 36.12" (SFF)	Shipping weight (Gross)	78lbs (35.38kg)		
Shipping package dimensions	D3600 - 11.13" x 23.75" x 38.12" (LFF)								
	D3700 - 11.13" x 23.75" x 36.12" (SFF)								
Shipping weight (Gross)	78lbs (35.38kg)								

Summary of Changes

Date	Version History	Action	Description of Change
04-Dec-2017	From Version 24 to 25	Changed	Overview, At a Glance, D3000 Enclosure Components, and Configuration Information were revised.
23-Oct-2017	From Version 23 to 24	Changed	Care Pack naming and Service and Support- Parts and Materials updated.
25-Sept-2017	From Version 22 to 23	Changed	Changes made throughout QuickSpecs.
07-Aug-2017	From Version 21 to 22	Changed	Changes made throughout QuickSpecs.
11-Jul-2017	From Version 20 to 21	Changed	Changed made to the entire document
27-Mar-2017	From Version 19 to 20	Changed	SKUs added and some other deleted.
28-Nov-2016	From Version 18 to 19	Changed	Changed made to the entire document
30-Sept-2016	From Version 17 to 18	Changed	Changes made in the Configuration Section
13-May-2016	From version 16 to 17	Changed	Changes made to the Product Highlights and Configuration Info Sections.
23-Oct-2015	From Version 15 to 16	Changed	Changes made to the Product Highlights and Configuration Information Sections.
02-Oct-2015	From Version 14 to 15	Changed	Changed made to the Overview and Configuration Information Sections.
04-Sept-2015	From Version 13 to 14	Changed	Changed the firmware from 2.02 to 1.72
10-Jul-2015	From Version 12 to 13	Changed	Changed the Step 4 in the Configuration Information Section. SKUs descriptions were updated.
01-Jun-2015	From Version 11 to 12	Changed	Changes made to the D3000 Enclosure Components, At a Glance, Product Highlights, Configuration and Overview Sections
30-Mar-2015	From Version 10 to 11	Changed	Changes made to the D3000 Enclosure Components, At a Glance, Product Highlights and Configuration Sections.
13-Feb-2015	From Version 9 to 10	Added	added the new 12G HDDs, Obsolete SKUs removed and SKUs descriptions updated
12-Dec-2014	From Version 8 to 9	Changed	Changes made to the Configuration Information section, SKU descriptions were updated, Obsolete SKUs were removed.
1-Dec-2014	From Version 7 to 8	Changed	Changes made through all QuickSpecs.
3-Oct-2014	From Version 6 to 7	Changed	Changes made through all QuickSpecs.
22-Aug-2014	From Version 5 to 6	Changed	Updated the following: What's new; At a Glance - Affordable, low cost Storage - D3600 maximum storage changed from 48TB to 72TB and 384TB to 576TB; D2000 enclosure components - High Levels of Storage Density, Data

Summary of Changes

			Protection and Functionality - changed 48TB to 72TB and 4TB to 6TB; Configuration Information - Step 4 Choose Hard Drives - added 737261-B21, 737394-B21, 765424-B21, 759208-B21, 759210-B21, 759212-B21, 761477-B21, 753874-B21
13-Aug-2014	From Version 4 to 5	Changed	Formatting Change
16-May-2014	From Version 3 to 4	Changed	At A Glance and Configuration Information were revised.
18-Apr-2014	From Version 2 to 3	Changed	Product descriptions were revised.
11-Apr-2014	From Version 1 to 2	Added	HPE Smart Array P431/4GB FBWC 6GB=2 ports Ext SAS Controller was added to Smart Array Controllers Supported.

